



# CRV 1014 Quad

10,2“ LCD TFT monitor with quad function

10,2” LCD TFT monitor with quad function

WEITERE INFOS



## Features:

- Sturdy 10,2” (25,9 cm) LCD TFT monitor especially designed for construction vehicles and trucks
- Built-in quad control box function for up to 4 cameras
- 4 camera inputs
- Built-in speaker
- Automatic adjustment of the display mode according to the quantity of connected cameras
- Single/split/quad view selectable, triple view applicable when 3 cameras are connected
- Automatically switches to the camera when triggered  
Trigger priority: CAM 1 > CAM 2 > CAM 3 > CAM 4
- On Screen Menu (OSD) with 7 languages
- PAL/NTSC switch
- Mirror/normal switch separate for each camera
- Incl. monitor stand

Technische Änderungen und Irrtümer vorbehalten.



# CRV 1014 Quad

10,2“ LCD TFT monitor with quad function

10,2“ LCD TFT monitor with quad function



## Technical data:

- 10,2“ TFT LCD monitor
- Digital display with LED backlight
- Antireflection display
- Auto dimmer
- Normal/mirror switch
- Viewing angle: up/down: 40°/60°; left/right: 65°/65°
- Brightness: 350 cd/m<sup>2</sup>
- Contrast: 300
- Resolution: 384.000 pixel
- Color system: PAL/NTSC
- Power-on function
- 4 x camera input
- 1 x audio input
- 2 x video output
- Power supply: 10 to 30 V
- Power consumption: 5 W
- Operating temperature range: -20 °C to +70 °C
- Storage temperature range: -30 °C to +80 °C
- E-Mark, RoHS compliant
- Dimensions (LxWxD): 255 x 183 x 42 mm
- Weight: approx. 720 g

EAN 40 41044 220449