



CRV 5605 Set

Rear view video set

5,6" TFT LCD monitor with color-camera



WEITERE INFOS



Features:

- Rear view video set consisting of:
5,6" (12,4 cm) LCD-TFT monitor & rear view color-camera
incl. monitor stand, 20 m connection cable (WPC 6)
- Easy to install and stock (plug & play)
- For 12 V & 24 V application

Monitor:

- Rear view monitor with 2 camera inputs
- 7 languages OSD
- High resolution
- 2 individual trigger wires
- Power on at voltage
- Priority adjustable
- Day/night switch

Rear view camera:

- Sturdy rear view color-camera
- Camera viewing angle: 110°
- Camera protection class: IP68
- 6 x IR LED residual light amplifiers for better performance in dark areas (0,01 lux)

Special accessories (optional):

- Additional/spare camera DBC 114073 Basic

Technische Änderungen und Irrtümer vorbehalten.



CRV 5605 Set

Rear view video set

5,6" TFT LCD monitor with color-camera



Technical data:

Monitor

- 5,6" TFT LCD monitor: 4:3
- Wide viewing angle: r/l 65°, u/d 45°/65°
- High brightness: 300 cd/m²
- Resolution: 224.640 pixel
- Mirror/normal picture switch available
- Day/night sensor
- Built-in speakers
- Video system: PAL/NTSC (auto)
- Power supply: 12/24 V (+/- 10%)
- Power consumption: < 7 W
- Operating temperature range: -20 °C to + 70 °C
- Storage temperature range: -30 °C to + 80 °C
- Dimensions (LxWxD): 165x115x29 mm
- Weight: approx. 528 g
- Vibration resistant: > 5G

Camera

- Standard rear view camera
- Built-in microphone
- Automatic day/night switch
- IR LED beamer for high performance in dark areas (0,01 lux)
- Sony Color CCD chipset
- Resolution (pixel):
PAL:500(H)x582(V);NTSC:510(H)x492(V)
- Image size: ¼ inch
- Lens: 2,6 mm
- Viewing angle: 110° (diagonal)
- Protection class: IP68
- Salt and chemicals tested
- Signal / noise ratio: > 48 dB
- Horizontal resolution: 420 TV lines
- Power supply: 12 V (+/- 10%)
- Power consumption max: 2,5 W
- Operating temperature range: -30 °C to + 65 °C
- Storage temperature range: -40 °C to + 85 °C
- Dimensions (LxWxD): 76 x 73 x 85 mm
- Weight: approx. 259 g
- Metal housing: silver
- Vibration resistant: > 6G

EAN CRV 5605 Set **40 41044 220609**

EAN DBC 114073 **40 41044 220586**

EAN CRV 5605M (monitor) **40 41044 220777**