

CRV 7000 Quad Set

Rear view video set

7" TFT LCD monitor with color-camera and quad control box



WEITERE INFOS



Features:

- Rear view video set consisting of:
7" (17,78 cm) LCD-TFT monitor, control box & rear view color-camera
incl. monitor stand, 20 m connection cable (WPC 5)
- Easy to install and stock (plug & play)
- For 12 V & 24 V application

Monitor:

- Multi-functional 7" LCD TFT monitor with control box for up to 4 cameras
- Built-in speakers with volume control
- Resolution: 1440(B) x 234 (H)
- Screen splitting: 2, 3, 4 images
- Mirror/normal switch

Rear view camera:

- Sturdy rear view color-camera
- Wide viewing angle (diagonal 130°)
- Protection class IP69
- Minimum illumination (0 lux)


Control box:

- 4 camera inputs (CA1, CA2, CA3, CA4) (AXION 4 Pin mini DIN jacks)
- Individual auto switch on of each camera (4 x trigger wires)

Special accessories (optional):

- Additional/spare camera DBC 114036 SB

Technische Änderungen und Irrtümer vorbehalten.



CRV 7000 Quad Set

Rear view video set

7" TFT LCD monitor with color-camera and quad control box



Technical data:

Monitor

- Multi-functional 7" LCD TFT monitor with control box for up to 4 cameras
- Built-in speakers with volume control
- Video system NTSC/PAL (auto)
- Resolution: 1440(B) x 234 (H)
- Monitor adjustment: FULL & 16:9
- Screen splitting: 2, 3, 4 images
- Mirror/normal switch
- Contrast & brightness adjustment
- Day / night sensor
- Vibration resistant up to 5,5 G
- Protection class: IP54
- Working temperature range: -10 °C to +50 °C
- Dimensions (WxHxD): 197x138x32 mm

Control box

- 4 camera inputs (CA1, CA2, CA3, CA4) (AXION 4 Pin mini DIN jacks)
- A/V input & output (RCA)
- Power supply 10 V – 32 V DC
- Vibration resistant up to 5,5 G
- Individual auto switch on of each camera (4 x trigger wires)
- Dimensions (WxHxD): 154x105x23 mm

Camera

- 1/3" CCD color-camera
- IR LED beamer for high performance in dark areas
- Minimum illumination (0 lux)
- Electronic brightness adjustment
- Automatic electronic iris
- Wide viewing angle (diagonal 130°)
- Waterproof microphone
- Vandal- & waterproof (IP69)
- Power supply 12 V DC (of the monitor)
- Weatherproof AL. die-cast case with sun-shield/mounting bracket & screws
- 20 m connection cable (WPC 5) (with waterproof WPC connectors)
- Dimensions (WxHxD): 69x41x50,7 mm

EAN CRV 7000 Quad Set **40 41044 220647**

EAN DBC 114036 SB **40 41044 220753**