




CRV 7005 Set

Rear view video set

7" TFT LCD monitor with color-camera



WEITERE INFOS



Design made in Germany!

Features:

- Rear view video set consisting of:
7" (17,78 cm) LCD-TFT monitor, rear view color-camera
incl. monitor stand, 20 m connection cable (WPC 6)
- Easy to install and stock (plug & play)
- For 12 V & 24 V application

Monitor:

- Rear view monitor with 2 camera inputs
- 7 languages OSD
- High resolution
- 2 individual trigger wires
- Power On at voltage
- Priority adjustable
- Day/night switch
- Guide-lines engageable

Rear view camera:

- Sturdy rear view color-camera
- Camera viewing angle: 124°
- Camera protection class: IP69K
- 6 x IR LED residual light amplifiers for better performance in dark areas (0,01 lux)

Special accessories (optional):

- Additional/spare camera DBC 114073 Basic

Technische Änderungen und Irrtümer vorbehalten.



CRV 7005 Set

Rear view video set

7" TFT LCD monitor with color-camera



Technical data:

Monitor

- 7" TFT LCD monitor: 16:9 (7" = 17,78 cm)
- Wide viewing angle: r/l 80°, u/d 40°/60°
- High brightness: 350 cd/m²
- Resolution: 336.960 pixels
- Mirror/normal switch
- Day/night sensor
- Built-in speakers
- Video system: PAL/NTSC (auto)
- Power supply: 12/24 V (+/- 10%)
- Power consumption: < 7 W
- Operating temperature range: -20 °C to + 70 °C
- Storage temperature range: -30°C to + 80°C
- Dimensions (LxWxD): 200x115x29 mm
- Weight: approx. 400 g

Camera

- Standard rear view camera
- Built-in microphone
- Automatic day/night switch
- IR LED beamer for high performance in dark areas (0,01 lux)
- Sony color 1.3 Megapixel CMOS
- Resolution (pixel):
PAL: 1.3 Mio. Pixels / 1280H
- Image size: 1/3.2 inch
- Lens: 2,8 mm
- Viewing angle: 124° (diagonal)
- Protection class: IP69K
- Salt and chemicals tested
- Signal / noise ratio: > 46 dB
- horizontal resolution: 800TV-lines
- Power supply: 12 V (+/- 10%)
- Power consumption max: 2,5 W
- Operating temperature range: -30 °C to + 80 °C
- Storage temperature range: -40 °C to + 85 °C
- Dimensions (WxHxD): 76 x 73 x 85 mm
- Weight: approx. 360 g
- Metal housing: silver
- Vibration resistant: > 6G

EAN CRV 7005 Set **40 41044 220555**

EAN DBC 114073 **40 41044 220586**

EAN CRV 7005M (monitor) **40 41044 220784**